

AQUALISA



Vitalise® SLX

Vitalise® SL

Vitalise® s

Vitalise® Electric

shower range from Aqualisa

refresh your showering
experience with Vitalise®

Contents

Vitalise Electric the instantaneous electric shower range from Aqualisa.
Stylish, contemporary and bursting with features, you can be sure to find the
perfect shower for your bathroom.

Vitalise® SLX

Illuminated multi-function LCD display and easy to use
push button controls.

Pages 6 - 9

Vitalise® SL

Illuminated, easy to use push button controls.

Pages 10 - 13

Vitalise® S

Simple, easy to use controls, available in a choice of finishes

Pages 14 - 17

Vitalise® Comparison Checklist

A quick reference guide to the installation, safety and user features
of the Vitalise Electric range

Pages 18 - 19



Vitalise® SLX

Pages 6 - 9

refresh...



Vitalise® SL

Pages 10 - 13

renew...



Vitalise® S

Pages 18 - 19

revitalise.

Introducing the new Vitalise® range of electric showers from Aqualisa.

Refresh your mind, renew your body and revitalise your senses with Aqualisa's new range of stylish, instantaneous electric showers.

Bursting with user features, you can be sure to find the perfect Vitalise Electric shower to suit your everyday showering needs. Choose from 3 zesty shower ranges – Vitalise SLX, Vitalise SL and Vitalise S for a rejuvenating showering experience.



Vitalise® SLX

refresh...

This multi-function electric shower will tell you everything you need to know; the temperature you shower at, the length of time you spend in the shower and the heat setting you have selected. Transform the way you shower with Vitalise SLX.



Vitalise® SLX

- Simple, easy to use push button controls
- Illuminated multi-function LCD display
- 4 heat settings – Cold, Low, Medium and High
- Intelligent phased shutdown, which flushes residual hot water out of the system for the comfort and safety of the next user
- Choice of 3 impressive spray patterns
- Easy clean nozzles
- Choice of power ratings - 8.5kW*, 9.5kW* and 10.5kW*

* At 240V



Vitalise® SLX

USER FEATURES



Technical guide

INSTALLATION	
Inlet connection	15mm compression fitting
Outlet connection	½" BSP
Water entry points	Top, bottom & rear on right side of unit
Cable entry points	Top, bottom & rear on right side of unit
Supply voltage	230V – 240V
Minimum supplied dynamic pressure	0.07MPa (0.7bar) @ 8lpm
Maximum supplied dynamic pressure	1.0MPa (10bar)
Plumbing system	Cold mains
SAFETY FEATURES	
Intelligent phased shutdown	Flushes residual hot water out of the system when temperatures exceed the factory setting, avoiding water wastage whilst providing comfort & safety for the next user
Heat sensor	Sophisticated heat sensor automatically switches down the heat setting if an excessively high temperature is detected
Low pressure warning	Provides instant feedback via the LCD display in the event of water supply issues
Approvals	WRAS / BMA Water Label / BEAB / CE
POWER RATINGS	
Vitalise SLX	8.5kW*, 9.5kW* and 10.5kW* *At 240V



Vitalise Electric SLX with adjustable head – White/Chrome with Chrome kit

Vitalise® SLX

DIMENSIONS



Vitalise® SL

renew...

Stylish, fresh and easy to use, courtesy of the simple illuminated push button controls. The 'Power on' LED light lets you know when your shower is ready to use. Just step in and feel renewed with Vitalise SL.



Vitalise® SL

- Simple, easy to use illuminated push button controls
- 'Power on' LED to show when shower is ready to use
- 4 heat settings – Cold, Low, Medium and High
- Intelligent phased shutdown, which flushes residual hot water out of the system for the comfort and safety of the next user
- Choice of 3 impressive spray patterns
- Easy clean nozzles
- Choice of power ratings - 8.5kW*, 9.5kW* and 10.5kW*

* At 240V



Vitalise® SL

USER FEATURES



Spray patterns

Outer

Middle

Inner



Technical guide

INSTALLATION

Inlet connection	15mm compression fitting
Outlet connection	½" BSP
Water entry points	Top, bottom & rear on right side of unit
Cable entry points	Top, bottom & rear on right side of unit
Supply voltage	230V – 240V
Minimum supplied dynamic pressure	0.07MPa (0.7bar) @ 8lpm
Maximum supplied dynamic pressure	1.0MPa (10bar)
Plumbing system	Cold mains

SAFETY FEATURES

Intelligent phased shutdown	Flushes residual hot water out of the system when temperatures exceed the factory setting, avoiding water wastage whilst providing comfort & safety for the next user
Heat sensor	Sophisticated heat sensor automatically switches down the heat setting if an excessively high temperature is detected
Low pressure warning LED	Provides instant feedback in the event of water supply issues
Approvals	WRAS / BMA Water Label / BEAB / CE

POWER RATINGS

Vitalise SL	8.5kW*, 9.5kW* and 10.5kW* *At 240V
-------------	-------------------------------------



Vitalise Electric SL with adjustable head - White/Chrome with White/Chrome kit

Vitalise® SL DIMENSIONS



Vitalise® s

revitalise...

Simple and easy to use, revitalise your showering experience and choose from 2 new refreshing colour finishes. Enjoy simplicity at its best with Vitalise S.



Vitalise® s

- Simple, easy to use rotary controls
- 'Power on' LED to show when shower is ready to use
- 4 heat settings - Cold, Low, Medium and High
- Choice of 3 impressive spray patterns
- Easy clean nozzles
- Choice of white with chrome or white/chrome colour finishes
- Choice of power ratings - 8.5kW* and 9.5kW*

* At 240V



Vitalise® S

USER FEATURES



Technical guide

INSTALLATION	
Inlet connection	15mm compression fitting
Outlet connection	½" BSP
Water entry points	Top, bottom & rear on right side of unit
Cable entry points	Top, bottom & rear on right side of unit
Supply voltage	230V – 240V
Minimum supplied dynamic pressure	0.07MPa (0.7bar) @ 8lpm
Maximum supplied dynamic pressure	1.0MPa (10bar)
Plumbing system	Cold mains
SAFETY FEATURES	
Low pressure warning LED	Provides instant feedback in the event of water supply issues
Approvals	WRAS / BMA Water Label / BEAB / CE
POWER RATINGS	
Vitalise S	8.5kW* and 9.5kW* *At 240V



Vitalise Electric S with adjustable head – White with White/Chrome kit

Vitalise Electric S with adjustable head – White/Chrome with White/Chrome kit



Vitalise range comparison checklist...



Vitalise® SLX			Vitalise® SL			Vitalise® s			
VTE8521SLX Vitalise Electric SLX 8.5kW with adjustable head - White/Chrome with Chrome kit	VTE9521SLX Vitalise Electric SLX 9.5kW with adjustable head - White/Chrome with Chrome kit	VTE10521SLX Vitalise Electric SLX 10.5kW with adjustable head - White/Chrome with Chrome kit	VTE8521SL Vitalise Electric SL 8.5kW with adjustable head - White/Chrome with White/Chrome kit	VTE9521SL Vitalise Electric SL 9.5kW with adjustable head - White/Chrome with White/Chrome kit	VTE10521SL Vitalise Electric SL 10.5kW with adjustable head - White/Chrome with White/Chrome kit	VTE8520S Vitalise Electric S 8.5kW with adjustable head - White with White/Chrome kit	VTE9520S Vitalise Electric S 9.5kW with adjustable head - White with White/Chrome kit	VTE8521S Vitalise Electric S 8.5kW with adjustable head - White/Chrome with White/Chrome kit	VTE9521S Vitalise Electric S 9.5kW with adjustable head - White/Chrome with White/Chrome kit
£187.50 £225.00 (inc VAT)	£197.50 £237.00 (inc VAT)	£208.33 £250.00 (inc VAT)	£145.83 £175.00 (inc VAT)	£155.83 £187.00 (inc VAT)	£166.67 £200.00 (inc VAT)	£125.00 £150.00 (inc VAT)	£135.00 £162.00 (inc VAT)	£130.00 £156.00 (inc VAT)	£140.00 £168.00 (inc VAT)
INSTALLATION									
Inlet connection	15mm compression fitting	•	•	•	•	•	•	•	•
Outlet connection	½" BSP	•	•	•	•	•	•	•	•
Water entry points	Top, bottom & rear on right side of unit	•	•	•	•	•	•	•	•
Cable entry points	Top, bottom & rear on right side of unit*	•	•	•	•	•	•	•	•
Supply voltage	230V – 240V	•	•	•	•	•	•	•	•
Minimum supplied dynamic pressure	0.07MPa (0.7bar) @ 8lpm	•	•	•	•	•	•	•	•
Maximum supplied dynamic pressure	1.0MPa (10bar)	•	•	•	•	•	•	•	•
Plumbing system	Cold mains	•	•	•	•	•	•	•	•
SAFETY FEATURES									
Intelligent Phased Shutdown	Flushes residual hot water out of system	•	•	•	•				
Heat sensor	Safeguards user from high temperatures	•	•	•	•				
Low pressure warning	Feedback in the event of water supply issues	•	•	•	•	•	•	•	•
USER FEATURES									
Push button controls	Easy to use	•	•	•	•				
Power on indication	Lets you know when shower is ready	•	•	•	•	•	•	•	•
Illuminated multi-function LCD display	Tells you all you need to know	•	•	•					
4 Heat settings	Cold, low, medium and high	•	•	•	•	•	•	•	•
Separate heat settings & temperature controls	For the perfect shower	•	•	•	•	•	•	•	•
APPROVALS	WRAS, BMA Water Label, BEAB, CE	•	•	•	•	•	•	•	•
GUARANTEE	2 years	•	•	•	•	•	•	•	•

* Except 16mm bottom entry only.



Aqualisa Products Limited, The Flyer's Way, Westerham, Kent TN16 1DE

Customer Service and Technical Helpline: 01959 560010 Website: www.aqualisa.co.uk

Prices correct at time of print.

The company reserves the right to alter, change or modify the product specifications without prior warning. Please refer to the installation guides for technical information. Registered Trademark Aqualisa Products Limited.

Copyright © Aqualisa 2012. All rights reserved. No part of this brochure may be reproduced whether by copying or storing in any medium, electronic or otherwise, without the express permission of Aqualisa subject to any contrary provision under the Copyright, Designs and Patents Act 1988. Any unauthorised reproduction of any part of this brochure may lead to a civil claim for damages or criminal prosecution.

Q3269 Part no. 700549 Issue 02 Jan 13